



<b>High speed precision lathe machine LA 430, 530 Made in Taiwan</b>			
<b>Specification</b>	<b>430x1100</b>	<b>530x1100</b>	<b>530x1700</b>
Width of bed	300 mm		
Total travel of top slide	120 mm		
Swing over bed	Ø432 mm	Ø532 mm	
Swing over cross slide	Ø272 mm	Ø372 mm	
Swing in gap	Ø610 mm	Ø710 mm	
Gap width in front of face plate	150 mm		
Height of center from leg bottom	1080 mm (42 3/8")	1080 mm (46")	
Distance between centers	1100 / 1700		
Number of spindle speeds	12 steps		
Spindle bore	Ø58 mm		
Type of spindle nose	ASA-A1-6, D1-6		
Taper of spindle bore& center	MT. NO. 6 x No. 4		
Range of spindle speeds	35,52,75,110,160,230,330,490,650,950,1350,2000		
Lead screw diameter and pitch	35 4TPI or pitch 6 mm		
Range of inch threads	2~72		
Range of metric threads	6 mm: 0.2~14		
Number feeds	36 steps		
Range of longitudinal feeds	0.03~0.85 mm		
Range of cross feeds	1/2 of longitudinal feeds		
Tailstock quill diameter	Ø60 mm		
Total travel of tailstock quill	150 mm		
Taper in tailstock quill	No. 4		
Spindle drive motor	5 HP/ 7.5HP (opt.)		
Coolant pump motor	1/8		
Space required (L x X x H)	2300x1000x1400 mm		2900x1000x1400 mm
Net weight (approximat)	1600 kg	1700 kg	1900 kg